



## **E&H LAMINATING & SLITTING COMPANY**

**For Pricing and Information**  
**please contact:**  
**KIEPURA AVIATION CORP.**  
61 Church St.  
Littleton, NH 03561  
Tel: 603-444-3459 / Fax: 603-444-0790  
Toll Free: 1-888-522-8273  
(USA/Canada)  
Email: [jane@kiepuraaviation.com](mailto:jane@kiepuraaviation.com)  
[www.kiepuraaviation.com](http://www.kiepuraaviation.com)

### **E&H #770-3FRD**

#### **PRESSURE SENSITIVE INSULATION COVER SPLICING TAPE**

**INTENDED USE:** This tape is primarily used in the fabrication of insulation blanket covers and for the installation of insulation blankets. It may be used for sealing sewn seams and for closing fabrication slits or holes around brackets, conduits or other objects that may exist after installation.

**CONSTRUCTION:** .0005 Mil Metalized Tedlar  
10x10 visual scrim count  
with fire retardant acrylic pressure sensitive adhesive

**PSTC-1 PEEL STRENGTH:** On FR Primed Aluminum

15Mil	54.4 oz/inch average
3 Day	129.6 oz/inch average
30 Day	152.3 oz/inch average

**WEIGHT:** 4.2 oz/square yard

**FLAMMABILITY:**

Burn Length	3.4 inches maximum
Flame Time	0 Seconds
Drip Flame Time	No Drips

**SHELF LIFE:** Minimum of 12 months in cool, dry storage

**PASSES SPECIFICATIONS:**

- FAR PART 25-853 (A,B)
- FAA Radiant Heat Panel FAR 25.856
- DMS-1511 12 Second Vertical Burn
- BSS-7230 12 Second Vertical Burn
- DMS-1984 Rev. P Type 6 Class 2
- BMS 5-149 Rev. A Type I Class 3 Grade A Form I

**E&H CO:** As manufacturer warrants that the products described and presented herein are of merchantable quality, but does not warrant their fitness for any particular use or make any other warranty, expressed or implied. Liability of **E&H** under this warranty is limited to replacement of the products found to be defective, or, at its option, a refund of the purchase price.